



NOTES:

FUSES REQUIRED FOR ALL INSTALLATIONS
 DIODE REQUIRED ACROSS COILS / RELAYS
 ASSUMES FOOTSWITCH IS OPEN WHEN THROTTLE OFF
 MR752 (OR 6A06) SERIES DIODE MUST CARRY 6AMP CONTINUOUS, 15AMP SURGE

REVISIONS			
REV.	ECO.	DATE	APVD
H	070706	070706	TT
J	072406	072406	TT
K	102706	102706	TT
L	110306	110306	TT
M	010907	010907	TT

DWG SCALE: NTS		DATE: 7/24/2006	
DRAWN: T.Thorne	ENGR: D.Crockett	7/20/2006	
PROPRIETARY THIS DESIGN IS THE PROPERTY OF ALLTRAX INC. REPRODUCTION OR TRANSMISSION OF THIS DESIGN IN WHOLE OR PART WITHOUT WRITTEN PERMISSION OF ALLTRAX INC.			
TITLE: DCX to Fairplay Diagram		REV. M	
SIZE: DOCUMENT NO. Doc100-017		REV. M	
FILE: _DWG-DCX-FM-Fairplay-cor-Page-1		SHEET 1 of 2	

DO NOT SCALE DRAWING

SEE PAGE 2
 VEHICLE
 WIRING

PART NO. ECG10907
 CHANGE B - SYMBOL