



PIN LOCATION 插孔点	WIRE DESIGNATION 导线标记	WIRE COLOR 导线颜色	REMARKS 注意
1	S1 (U1)	WHITE白	--
2	S2 (U2)	GREEN绿	--
3	S3 (U3)	BLUE蓝	--
4	GND (0)	BLACK黑	SHIELD TIED TO THIS PIN
5	V _{cc} (+12)	RED红	--

NOTES:

- 1.CCW
- 2.TURNS IS 20 PER PHASE
- 3.Front bearing: NTN6006 LLUC3/5K (Made in Japan)
- 4.Product to be shipped in plain white box, styrofoam packaging
Include Dyno Plot in box.
- 5.Box to be marked: Part Number: ME 1012 REV-A
Made in China
- 6.150°C magnet
- 7.Motor Phase Resistance is 0.0048Ω

NAMECARD DATA
 PART # ME1012 REV-A
 DATE CODE XXXXXX
 SERIAL #:XX.XX.XXXX
 Motenergy,Inc.
 Slinger, WI USA

REV.	CHANGES	BY	ECO NO.	DATE	DO NOT SCALE DRAWING THIS DRAWING IS PROPRIETARY PROPERTY OF MOTENERGY,INC CORPORATION DISCLOSED IN CONFIDENCE, WHICH MAY NOT BE USED OR DISCLOSED WITHOUT PERMISSION. RETURN PROMPTLY AFTER USE.	DIMENSIONING AND TOLERANCING PER ANS Y14.5M-1994	MATERIAL	TITLE	Motenergy, Inc. Slinger, WI USA	
A	change to 150C magnet, decrease winding resistance,the length of motor short 4mm,shorten the cooling slots to 1/2	LXP	-	12.04.24				OUTLINE		
-	-	-	-	-				DRAWN: lxp	12.04.24	
-	-	-	-	-				APPR:		DESIGN VENDOR: -
-	-	-	-	-				MODEL NO:		OJW.T. 301.552
-	-	-	-	-				SCALE: -		REV A SHEET 1 OF 1